



ard f.lli raccanello s.p.a. industria vernici e smalti

TECHNICAL SHEET **138**

CODE 0.710

creative desert stone

Coarse sand effect decorative finish (water based).

GENERAL

CREATIVE DESERT STONE is a special water based sandy metallic paint with luminescent gold or silver effects for interiors. Its silver or gold sand metallic effects have been devised for interior design.

PROPERTIES

Surfaces decorated with CREATIVE DESERT STONE offer a harmonious balance between aesthetically pleasing effects & personal taste.

It is recoatable with any of our latex paints, odourless, dust repellent, never yellows, stays clean and guarantees maximum comfort and well-being just a few hours after application.

INSTRUCTIONS

Substrate preparation:

Interior walls (bare or with distemper paintwork): ensure the substrate has at least 28 days weathering. Use a soft brush to remove dust and unsound plaster. Level any imperfections with LITOSTUCCO adding as required.

Allow 6 hrs, sand the stuccoed areas and clean thoroughly.

The choice of sealer and dilution depends on the condition of the substrate, ARDFIX is fine in most cases.

Ensure the surface is dry & apply one or more layers of CREATIVE FONDO (white) to obtain an homogeneous appearance.

Allow 6 hrs and proceed with CREATIVE DESERT STONE.

Wooden surfaces & bare plasterboard panels: clean the polished surface and fill any imperfections (knots, joints, nails, cracks etc.) with LITOSTUCCO. Sand, clean and apply one or two hands of a CREATIVE FONDO (white). Allow 6 hrs & apply CREATIVE DESERT STONE.

Surfaces with CREATIVE ARD SAND paintwork: accurately wash the surface with normal powder detergents and rinse well with water. Allow the surface to dry perfectly & apply a layer of CREATIVE FONDO. Allow 6 hrs & apply CREATIVE DESERT STONE.

Application:

This product is ready for use (thinning - at 10% in water volume - **may be required** according to the type of substrate and environmental conditions). The aesthetics vary according to the application technique employed.

- **SAND EFFECT:** use a brush to apply, in different directions, an uneven coat. Before the product dries, delicately brush again with a *discharged brush* to obtain a soft/veil distribution.
- **LINE EFFECT:** use a brush to apply an even coat. Before the surface dries, brush again in a vertical fashion from bottom to top.
- Remove protective tape and clean equipment immediately with plenty of water.
- Do not apply when the ambient humidity causes condensation or in over heated environments.
- If different batches are used, mix the same in order to avoid aesthetical differences.
- Store above freezing; do not apply below + 5°C.
- Use in compliance with the current Health & Safety Regulations. Dispose of spent material/containers according to the same.

TECHNICAL DATA

SPECIFIC WEIGHT	1060 ± 50 g/l	
VISCOSITY AT 20 °C	11000 ± 3000 cP	
DRYING AT 20 °C *	TOUCH DRY	4 hrs
	IN DEPTH	24 hrs

YIELD

The coverage may vary according to the substrate's roughness. Coverage as per colour show card is 8-9 m²/l.

SPECIFICATIONS

Coarse sand effect decorative finish (water based).

Application (brush/roller/topcoat) on treated interior surfaces of a odourless, hydrodilutable decorative coating based on special binders & pearlescent pigments type CREATIVE DESERT STONE with a consumption, which varies from 0.11 to 0,13 l/m².

€/m²

The data herein were correct at the time of Quality Control and refer to standardized environmental conditions.
The same are to be considered as a guide.
Revision 2015/06



ard · f.lli raccanello s.p.a. · industria vernici e smalti

35129 PADOVA – Zona Ind.le Nord 1^a Strada, 13 – Tel. 049.8060000 (5 linee)
Fax 049.773749 – www.ard-raccanello.it – e-mail: ardsipa@ard-raccanello.it